

IR thermal camera

MD 9910 IR thermal camera with Bluetooth

IR thermal imager



MD 9910 is a small thermal imager with large ambitions. Frame rate is extremely fast at 50 Hz. 80x80 pixel thermal resolution can show damage on contacts in electrical switchboards or distribution boards, stressed overcurrent or overvoltage protection, or unnecessary friction on motor axle. PCB troubleshooting is made easier by discovering hot spots at close range. At the same time, short focal length allows to go through large areas quickly. Center shot temperature, hot and cold markers give a better sense to the image and its span. Shot images can be immediately transferred to Android device using the app and Bluetooth connection. Span can be set manually to be able to take advantage of its great thermal resolution. Large Li-ion battery allows for 4 to 5h work. It was drop-tested to 2m.



80 x 80
pixels

MEASUREMENT FUNCTIONS:

- Temperature,
- Temperature difference.

KEY FUNCTIONS:

- Very fast frame rate 50 hz,
- Three markers on screen (hottest, coldest, central),
- 5 different palletes,
- Lock and compare feature,
- Temperature in °C, °F or K
- LED flashlight,
- Android and iOS apps for Bluetooth connection,
- Instant share of image over Bluetooth,
- Shooting images from Android/iOS app,
- PC software for image editing and report building included,
- Rechargeable Li-Ion batteries with long life,
- Internal memory,
- Hold image feature,
- PC software.

APPLICATIONS:

- Troubleshooting electrical installations (switchboards, contacts, busbars, etc.)
- Troubleshooting electrical equipment (motors, transformers, etc.),
- Building and facility maintenance,
- Field service,
- Energy loss analysis,
- Troubleshooting other installations (pipes, carpentry, windows, etc).

TECHNICAL SPECIFICATION

FUNCTION	
IR sensor resolution	80x80 pixel
Temperature range	-20 – 380°C
Thermal sensitivity/NETD	0,1°C @ 30°C / 100 mK
Thermal accuracy	Higher value $\pm 2^\circ\text{C}$ or $\pm 2\%$
Field of vision	21 x 21°
Spectral range	8 – 14 μm
Emmissivity	0.01 – 1.0
Frame rate	50 Hz
Focal length	7,5mm
Spatial resolution	4,53 mrad
Min focus distance	0.5m
Focus	Fixed
Display resolution	240x320 pxl
Color palettes	5
Data storage	20 images
Data communication	Bluetooth
Storage image format	Bmpwith temperature and emissivity
Operating temperature	-10°C – 45°C
Storage temperature	-30°C – 55°C
Humidity (storage and operation)	< 80%
Weight	260g
Size	180mm x 60mm x 75mm

ORDERING INFORMATION



Standard set (MD 9910)

- MD 9910 IR thermal camera
- Software CD
- AC adapter
- Non-slip strap
- Carrying case
- Instruction manual

METREL D.D.

Measuring and Regulation Equipment
Manufacturer
Ljubljanska 77, SI-1354 Horjul, Slovenia
T +386 (0)1 75 58 200, F +386 (0)1 75 49 226
metrel@metrel.si, www.metrel.si

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery.
Subject to technical change without notice.